

# IMAGING WAREHOUSE

## COPISCAN 4040D

Higher performance, heavy-duty production capabilities and State-of-the-art image quality have always been characteristics of high volume centralized production scanners. The Copiscan 4040D redefines the low-end and midrange categories, bringing today's workgroups these high performance features, such as daily duty cycles 3 times that of the nearest competing scanner, duplex imaging speeds up to 80 images per minute, a sleek new look - yet all at an affordable desktop price.



Now workgroup users can take advantage of scanning mixed batches in a wide range of paper and sizes, duplex imaging, highly consistent scanning due to self-calibrating electronics, and Adaptive Contrast Enhancement (ACE Plus) technology for "better-than-original" scanning. Best of all, the Copiscan 4040D is a turnkey solution, complete with ISIS certified drivers for easy integration.

Plus, users can always count on the rugged construction and unbeatable reliability for which Bell & Howell is known. You'd expect nothing less from the company consistently consumer-rated #1 in Reliability, Ease of Operation, Service and Technical Support and Paper Handling as described in a recent user survey.

### Specifications

**Style: Duplex**

**Throughput Rate: Portrait 40 ppm (80 ipm)**

**Resolution : 200, 240, 300 dpi**

**Document Sizes: Automatic Feed: MIN: 2 1/4" x 2 1/4" , MAX: 8 1/2" x 14**

**Manual Feed: MIN: 2 1/4" x 2 1/4" , MAX 8 1/2" x 14"**

**Document Thickness: Single sheet 0.0018" to 0.0080" (Onion skin to card stock)**

**Feeder Capacity : 50 sheet capacity/Automatic feed (.20") Mode user selectable**

**Host Interface: SCSI**

**Image composition: 1 bit binary, 8 bit grayscale**

**Compression: Group 3, Group 4, J-BIG**

**Image processing: dynamic thresholding,**

**4x4 & 8x8, dithering, error diffusion**

**Image Enhancement : ACE+ standard**

**Daily Duty Cycle : 3,000 sheets per day**

**Electrical Requirements : 115-230 VAC auto sensing, 50-60 Hz**

**Size : Height: 9.25" Width: 19.5" Depth: 25.5" (w/feeder)**

**Weight : 45 lbs.**

**Agency Recognition : CE MARK, UL1950; CUL/CSA 22.2 NO. 950-90; TUV EN 60950, FCC CLASS A;  
EN50081-1/CISPR22 CLASS B; EN50082-2/IEC801 -2, -3, 4; VCCI CLASS 2**

**Bundled Components : ISIS driver**

**1-800-97PIXEL**