

KV-SS855D High Speed Scanner




The Perfect Solution for Handling Large Volumes

The KV-SS855D is the latest addition to Panasonic's family of world-class production scanner products. It provides you with high-end production scanning with the quality and speed you would expect from a much more expensive scanner. The KV-SS855D employs new roller material that offers quieter paper intake and improved paper handling. Scanning at an incredible rated speed of 85 ppm, a 1000 page automatic document feeder, and capable of handling paper from onionskin to cardstock - in mixed batches - will save you time and money. If your original documents are an irregular size or less than perfect, the KV-SS855D can handle it - business cards, invoices, checks, even wrinkled documents. The KV-SS855D is the perfect solution for virtually any large volume scanning situation.

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©2000 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t



www.panasonic.com/scanners

KV-SS855D Specifications

Scanning Face	Duplex Scanning (front and back sides)
Scanning Method	Front: CCD, Back: CCD
Scanning Speed	85 pages/minute at 200 dpi (simplex) 160 ipm at 200 dpi (duplex) Landscape: 95 ppm at 200 dpi (simplex) 187 ipm at 200 dpi (duplex)
Scanning Resolution	100 dpi to 400 dpi
Auto Document Feeder	1,000 pages
Image Enhancement Technology	Brightness / Contrast, Grayscale, White Level Follow, Subwindows, Halftone Processing, Image Emphasis, Monochrome Reversing, Auto Threshold, Auto Separation, Patch Code, Bar Code, Long Paper, Double Feed Detection
Image Compression	Group 3, Group 4 and JBIG
Tonal Gradation	Binary Mode, 64 step gradation (dither mode) Binary Mode, 64-step gradation (error diffusion mode)
Paper Size	1.9" x 3.3" to ledger 11.7" x 17"
Paper Thickness	2.0 to 7.9 mils., single feed 2.4 to 5.9 mils., continuous feed
Paper Weight	11 to 42 lbs., single feed 13 to 42 lbs., continuous feed
Dimensions	22.4" W x 21.5" D x 16.3" H
Weight	110 lbs.
Power Requirement	120 VAC, 60Hz
Power Consumption	1.3A maximum scanning, .5A (standby)
Operating Environment	59°F to 86°F; 10% to 80% RH
Storage Environment	32°F to 95°F; 10% to 80% RH
Accessories	KV-SS03 Cleaning Kit, KV-SS05 Imprinter (Post Scan, 72 characters), KV-SS06 Ink Cartridge, KV-SS040 Red Lamp, KV-SS041 Roller Exchange Kit

Features

- **Panasonic Image Enhancement Technology**
 - White Level
 - Brightness / Contrast
 - Bar code and Patch code
 - Grayscale
 - Length Control
- **KOFAX- Adrenaline Certified**
- **Expanded memory capability**
- **ISIS® Certified Drivers and TWAIN Compliant**
- **High-speed production scanning**
- **1000 page ADF**
- **Up to 400 dpi optical resolution**
- **Post scan imprinter option**
- **Length Control**