

fi-6130Z/fi-6230Z

Color Duplex Workgroup Scanners

Enhanced for the ultimate in
performance and reliability



- Fast 40ppm / 80ipm scanning in color, grayscale, and monochrome
- Exceptional 300 dpi color scanning at 30ppm / 60ipm
- Advanced paper handling technology for the ultimate in feeding reliability
- Robust 50-page Automatic Document Feeder (ADF)
- Plastic and embossed card scanning
- Scanner Central Admin Suite
- Comes with Kofax® VRS® Professional and ScandAll PRO 2.0

FUJITSU

fi-6130Z & fi-6230Z

Designed with innovative features, the Fujitsu fi-6130Z and fi-6230Z scanners offer outstanding price/performance value in a compact footprint, conserving both space and budget.

Scanning Performance


With duplex scanning speeds of up to 80 images per minute in Color, Grayscale, and Black & White, the fi-6130Z and fi-6230Z also delivers uncompromised high-resolution performance of up to 60 images per minute at an astounding 300 dpi resolution for high accuracy OCR and bar code recognition. Combined with one of the most advanced paper separation features in their class, the fi-6130Z and fi-6230Z employ reversing roller technology and a host of intelligent functions to provide exceptional feeding reliability for a wide variety of document types.

- Continuous hard and embossed card scanning up to 1.4mm thick
- Ultrasonic Double-feed Detection sensor for security against lost images
- Intelligent Multi-Feed Function for efficiently scanning overlapped documents like taped receipts
- Paper Protection sensor to stop a jam before it happens
- Long document support up to 10 feet*

Centralized Efficiency

Whether the infrastructure is fixed or expanding, managing technology efficiently inside the organization is key to reducing total cost of ownership and the Fujitsu fi-6130Z and fi-6230Z provide system administrators with advanced software tools to centrally manage these scanners more productively and cost effectively.

- Agent, console and server remote scanner management
- Real-time Fujitsu scanner inventory
- Status and alert monitoring
- Centralized driver update deployment
- Consumable management



Fully Loaded One Box Solution

Fujitsu fi-6130Z and fi-6230Z workgroup scanners conveniently include everything in the box to get organizations up and scanning. With Kofax VRS® Professional and ScandAll PRO software users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch.

- Kofax VRS 5.0 Professional
- ScandAll PRO 2.0 batch scanning and PDF creation software
- ScanSnap mode for easy one button scanning (Add-in)

And the one-year Limited Warranty, along with eligibility for our Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all service programs, go to www.ImageService.com or call (800) 626-4686.

*With TWAIN driver

ScandAll PRO

Kofax
VRS
PROFESSIONAL



Advance
EXCHANGE

SCANAID

Fujitsu Computer Products of America, Inc. 1250 East Arques Avenue Sunnyvale, CA 94085-4701
(800) 626-4686 (408) 746-7000 • info@cpa.fujitsu.com • <http://us.fujitsu.com/fcpa>

FUJITSU

Technical Specifications			
Models		fi-6130Z (ADF only) / fi-6230Z (ADF+Flatbed)	
Image Sensor Type	fi-6130Z	Color CCD (Color Charge Coupled Device x 2)	
	fi-6230Z	Color CCD (Color Charge Coupled Device x 3)	
Light Source		White cold cathode discharge lamps	
Optical Resolution		600 dpi	
Output Resolution ¹	Color (24 bit)	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi ²	
	Grayscale (8 bit)		
	Monochrome		
Output Format		Color: 24-bit, 8-bit, 4-bit, Grayscale: 8-bit, 4-bit, Monochrome: 1-bit ³	
Internal Video Processing		1024 levels (10-bit)	
Image Processing Function	Hardware	Image emphasis, Error diffusion, Dither, Simplified DTC, Moire removal, Dropout color (R, G, B None, Specified)	
	Software	Multi-image output, Blank page skip, Advanced-DTC, sRGB, Auto color detection, Automatic page size detection, Hole punch removal, Tab cropping, Split image	
Performance			
Scanning Speed (A4, Portrait) ⁴	Color ⁵ , Grayscale ⁵ , Monochrome	ADF	Simplex: 40 ppm, Duplex: 80 ipm (200 dpi) Simplex: 30 ppm, Duplex: 60 ipm (300 dpi)
		Flatbed (fi-6230Z)	1.7 seconds (200 / 300 dpi)
ADF Capacity ⁶		50 Sheets (A4: 80 g/m ² or 20 lb.)	
Document size	ADF minimum	A8 Portrait: 2 x 3 in. (52 x 74mm)	
	ADF maximum ⁷	A4 Portrait: 8.5 x 14 in. (Legal)	
	Long document	8.27 x 120 in. (10 feet) ⁸ or 8.27 x 34 in.	
	Flatbed (fi-6230Z)	8.5 x 11.69 in. (216 x 297mm)	
ADF Feeding	Letter	11 to 56.2 lb. (41 to 210g/m ²)	
Paper Weight (Thickness)	A8 sheets	34 to 56.2 lb. (127 to 210g/m ²)	
	Card ⁹	Up to 1.4 mm (Portrait / Landscape) ¹⁰	
Interface		USB 2.0 (B-type)	
Physical Specifications			
Power requirements		100 to 240VAC ±10%	
Power consumption	fi-6130Z	38W or less (Sleep: 5.36W or less)	
	fi-6230Z	45W or less (Sleep: 5.36W or less)	
Dimensions (WxDxH) ¹¹	fi-6130Z	11.8 x 6.4 x 6.2 in. (301 x 160 x 158mm)	
	fi-6230Z	11.8 x 22.9 x 9.0 in. (301 x 567 x 229mm)	
Weight	fi-6130Z	9.24 lb. (4.2 kg) or less	
	fi-6230Z	19.36 lb. (8.8 kg) or less	
Environmental compatibility ¹²		ENERGY STAR® and RoHS	
Operating Environment	Temperature	42° to 95° F (5° to 35° C)	
	Relative humidity	20% to 80% (non-condensing)	
Inbox Contents		ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM, Getting Started Guide	
Bundled Software		TWAIN, ISIS™, Kofax VRS Professional, Software Operation Panel, Error Recovery Guide, ScandAll PRO 2.0 Std. with PDF edit, ScanSnap mode add-in, Scan to Microsoft Share Point, ABBYY FineReader for ScanSnap™, Scanner Central Admin	
Options		Post-scan Imprinter (fi-6130Z only), ScandAll PRO 2.0 Premium Upgrade, Carrier Sheet, Black Document Pad (fi-6230Z only)	
OS Support		Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows Server® 2003/2008 (32-bit/64-bit), Windows XP® (32-bit/64-bit)	
Feed Detection Features		Ultrasonic Double Feed Detection Sensor, Paper Protection Sensor, Intelligent Multi-Feed Function (Manual Bypass)	
Other Features		Embossed Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (in ADF only)	
Limited Warranty		One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.ImagingService.com or call (800) 626-4686.	
Service Options		Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables: ScanAid™ kit. For full details, visit www.ImagingService.com or call (800) 626-4686	
Part Number	fi-6130Z	PA03630-B055	
	fi-6230Z	PA03630-B555	

1 Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex. **2** Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher). **3** Color (4-bit & 8-bit with driver), Grayscale (4-bit with driver). **4** Actual scanning speeds are affected by data transmission and software processing times. **5** JPEG compressed figures. **6** Maximum capacity varies, depending upon paper weight. **7** Document sizes larger than A4, but not exceeding A3, can be scanned (single-side) using a carrier sheet. **8** The scanning of documents that exceed 34 inches in length will be limited to using TWAIN at 200 dpi or less. **9** Supports ISO7810 embossed cards. **10** Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.) **11** Excluding the ADF paper chute and stacker. **12** PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2002/95/EC).



©2011 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. Adobe and Acrobat are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft, SharePoint, Windows and Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ISIS is a registered trademark of Pixel Transistors, a division of Captiva Software Corporation. VRS is a registered trademark of Kofax Image Products, Inc. ABBYY FineReader are trademarks of ABBYY Software House. As an ENERGY STAR® Partner, Fujitsu Ltd. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a U.S. registered trademark. All other trademarks are the property of their respective owners. All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price and warranty, post-warranty and service programs. Printed in the U.S.A. Qty. 5M D395001111