The WideTEK 36CL-MF scanner forms the basis of all of the MF solutions and is the fastest, most productive wide format MFP solution on the market, running at 10 inches per second at 200 dpi in full color, at the lowest possible price. At the full width of 36" and 600 dpi resolution, the scanner still runs at 1.7 inches per second. WideTEK 36CL-MF is the best choice to build a powerful and high quality MFP with either an integrated printer series specific stand, a high stand or a standalone stand. All MFP solutions come with a built in closed loop color calibration function producing the best possible copies on your selected printer and paper combination.

Scanner Optics	CIS camera, scans in color, grayscale, B&W
Resolution	1200 x 1200 dpi scanner resolution 9600 x 9600 dpi interpolated (optional)
Document Size	965 mm (38 inch) width, nearly unlimited length Scans 915 mm (36 inch) widths
Scanning Speed	200 dpi - 15 m/min (10 inch/s) in color 600 dpi - 8 m/min (5 inch/s) in grayscale
Color Depth	48 bit color, 16 bit grayscale
Scan output	24 bit color, 8 bit grayscale, bitonal, enhanced halftone
Output Formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG), AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data
Size H x W x D & Weight	170 x 1088 x 358 mm (6.7 x 42.8 x 14.1 inches) 24 kg (53 lbs.)
Quality (min.)	ISO 19264-1 level B, FADGI ***
Power Consumption	< 0.5 W (Sleep) / 5 W (Standby) / <25 W (Ready to scan) / <45 W (Scanning)

WideTEK®36CL-MF



- √ Face up scanning with on the fly rotation and modification
 of images without rescanning. Automated crop & deskew.
- Built in closed loop color calibration function for best possible copies
- ✓ LED lamps, no warm up, IR/UV free
- ✓ Large 21" full HD color touchscreen for simple operation in optional bundles
- √ Scan2USB, FTP, SMB and Network. Copies and emails directly. Touchscreen enabled ScanWizard, PrintWizard and Easyscan
- ✓ LED illumination, sturdy steel document scanning bed
- ✓ Fastest scan in color: 10 inches/second at 200 dpi, full width
- √ Easy installation via Scan2Net® technology