

SureColor® P7000



Professional 24" large-format 10-color inkjet printer.

Print your legacy — professional 24"-wide printer for photographic, fine art and commercial proofing applications

UltraChrome HDX™ Inks — professional 10-color archival pigment ink set delivers best-in-class color gamut with higher-density blacks for enhanced overall dynamic range, contrast ratio and clarity for both color and black-and-white prints

Exceptional print permanence — Standard Edition printer offers next-generation pigment ink technology with Light Black ink for up to twice the overall print permanence than previous generations¹

Commercial Edition — features an all-new Violet ink for expanded color gamut with up to 99 percent PANTONE® FORMULA GUIDE solid-coated color-matching accuracy, ideal for all commercial and flexographic proofing applications

Remarkable detail — Epson® PrecisionCore® TFP® printhead delivers high print speeds with 360 nozzles per color channel with variable-size ink droplets as small as 3.5 picoliters

Superior connectivity — standard gigabit Ethernet and USB 2.0 along with an optional internal 320GB print server quickly transfers print jobs and frees up workstations; the internal print server includes print queue management and the ability to save and reprint jobs

Designed for use exclusively with Epson cartridges.*



SureColor® P7000

Print

Printing Technology Advanced PrecisionCore TFP 10-channel, drop-on-demand printhead with ink-repelling coating technology Ink Type UltraChrome HDX pigment ink; 11-ink, 10-color

Standard Edition ink configuration: C, LC, VM, VLM, Y, LK, LLK, O, G and PK or MK

Commercial Edition ink configuration: C, LC, VM, VLM, Y, LK, V, 0, G and PK or MK

Fade Resistance/Print Longevity¹ Color: up to 200 years; black-and-white: up to 400 years

Nozzle Configuration Color and monochrome heads; 360 nozzles x 8

Droplet Technology Smallest droplet size: 3.5 picoliters; Variable Droplet Technology can produce up to three different sizes per line

Maximum Resolution 2880 x 1440 dpi

Printer Speed²

16" x 20" prints from 2:02 to 6:58; normal is 4:16 20" x 30" prints from 3:40 to 12:25; normal is 7:36 40" x 60" prints from 11:15 to 40:05; normal is 24:20

Printer Language/Drivers Epson ESC/P® raster photographic drivers standard

Auto-switching Black Ink Technology³

Black Ink Conversion Times

Matte to Photo Black: approx. 2:55 Photo to Matte Black: approx. 2:07

Ink Used During Conversion

Matte to Photo Black: approx. 7.2 mL Photo to Matte Black: approx. 1.12 mL

Epson Intelligent Ink Cartridges4

In-box Cartridge Fill Volume 110 mL each color x 11 colors total

Retail Cartridge Fill Volume 150, 350 or 700 mL each color x 9 colors total

Ink Cartridge Shelf Life 2 years from printed production date or 6 months after opened

Printer is designed for use with Epson cartridges only, not third-party cartridges or ink. www.epson.com/cartridgereturn*

Roll Media Handling

Single Top-loading Roll 24" wide

2" or 3" Core Diameter User-adjustable roll media adapters Roll Cutting⁵ High-speed internal rotary cutter; auto or manual

Minimum Auto Cut Length 5.0" plus top and bottom margin (5.24" min.)

Top/Bottom Margins (mm) Normal: 20/15; option: 35/15, 150/15, 15/15, 3/3

Left/Right Margins 3 mm each side; 0.24" total; or 0" at BorderFree® sizes

Roll Paper Remaining Printable barcode tracking system

Sheet Media Handling

Single Sheet, Top-loading Up to 24" wide Sheet Loading Auto-loading if less than 0.5 mm thick Media Thickness 0.8 mm to 1.5 mm

Sheet Media Handling (continued)

Top/Bottom Margins 3 mm/15mm

Top/Bottom Margins with Centering On 15 mm/15 mm Left/Right Margins 3 mm each side; 6 mm or 0.24" total BorderFree Print Widths 10", 11.8", 13", 16", 17", 20.3", 24"

Printable Area and Accuracy

Maximum Paper Width 24

Minimum Cut-sheet Size~8.5"~x~11"

Maximum Printable Roll Length⁶ 529"

Line Accuracy +/- 0.2% of specified length (+/- 0.26 mm min.)

Printer Interfaces⁷

Hi-Speed USB 2.0 (1 port) 1000Base-T Ethernet (1 port)

Operating Systems Supported

Apple® OS X® 10.11.x, 10.10.x, 10.9.x, 10.8.x and 10.7.x Windows® 10, 8.1, 7 (32-bit, 64-bit)

General

Weight and Dimensions (W x D x H)

Basket closed: 53.4" x 26.3" x 48" (1356 x 667 x 1218 mm) Weight: 223 lb (101 kg)

Acoustic Noise Level

Less than 47 dB(A) according to ISO 7779

Temperature

Operating: 50 ° to 95 °F (10 ° to 35 °C)

Operating (recommended): 65 $^{\circ}$ to 75 $^{\circ}\text{F}$ (18 $^{\circ}$ to 24 $^{\circ}\text{C})$

Storage: -4 $^{\circ}$ to 104 $^{\circ}$ F (-20 $^{\circ}$ to 40 $^{\circ}$ C)

Relative Humidity

Operating: 20 - 80% (no condensation)

Operating (recommended): 45 - 60% (no condensation)

Storage: 5 - 85% (no condensation)

Electrical Requirements

Voltage: AC 110 - 240 V Frequency: 50 - 60 Hz Current: 2 A

Printing: approx. 65 W

Ready: approx. 19 W

Sleep Mode: approx. 2 W (1000 BaseT Ethernet in Standby) Power Off: less than 0.5 W ENERGY STAR® qualified

Standards and Approvals

Safety standards: UL605950-01, CAN/CSA C22.2 No. 60950-1 EMC FCC part 15 subpart B class B, CAN/CSA-CEI/IEC CISPR22 class B,

AS/NZS CISPR 32 class B Limited Warranty and Service Standard one-year usually next-business day on-site repair with toll-free phone support Monday through Friday

Country of Origin China

Ordering Information

SureColor P7000 Standard Edition SCP7000SE **SureColor P7000 Commercial Edition** SCP7000CE T699700 Maintenance Tank Replacement Printer Cutter Blade C12C815331 Additional Roll Media Adapters (pair) C12C811241 Internal Print Server 320GB C12C848031 24" SpectroProofer® UVS SPECTR024UVS Replacement X-Rite® ILS30EP (for SpectroProofer) C12C932021

UltraChrome HD Ink (150 mL)

Photo Black Ink Cartridge

Cvan Ink Cartridge

nL) T54Vxxx

T834100
T834200
T834300

Vivid Magenta Ink Cartridge T834300
Yellow Ink Cartridge T834400
Light Cyan Ink Cartridge T834500
Vivid Light Magenta Ink Cartridge T834600
Light Black Ink Cartridge T834700
Matte Black Ink Cartridge T834800
Light Light Black Ink Cartridge T834900

UltraChrome HDX Ink (150 mL)

Orange Ink Cartridge T834A00 Green Ink Cartridge T834B00 Violet Ink Cartridge T834D00

UltraChrome HD Ink (350 mL) T54Xxxx

Photo Black Ink Cartridge T824100 Cyan Ink Cartridge T824200 Vivid Magenta Ink Cartridge T824300 Yellow Ink Cartridge T824400 Light Cvan Ink Cartridge T824500 Vivid Light Magenta Ink Cartridge T824600 Light Black Ink Cartridge T824700 Matte Black Ink Cartridge T824800 T824900 Light Light Black Ink Cartridge

UltraChrome HDX Ink (350 mL)

 Orange Ink Cartridge
 T824A00

 Green Ink Cartridge
 T824B00

 Violet Ink Cartridge
 T824D00

UltraChrome HD Ink (700 mL) T55Kxxx

Photo Black Ink Cartridge

New Ink #

T804100

Cyan Ink Cartridge

New Ink #

T804200

 Vivid Magenta Ink Carriage
 T804300

 Yellow Ink Cartridge
 T804400

 Light Cyan Ink Cartridge
 T804500

 Vivid Light Magenta Ink Cartridge
 T804600

 Light Black Ink Cartridge
 T804700

 Matte Black Ink Cartridge
 T804800

 Light Light Black Ink Cartridge
 T804800

UltraChrome HDX Ink (700 mL)

Orange Ink Cartridge T804A00
Green Ink Cartridge T804B00
Violet Ink Cartridge T804B00
Purchase the cartridge size that will most likely be consumed within 6 months of installation in the printer.

Extended Service Plans

One-year Epson PreferredSM Plus Service EPP900B1 Two-year Epson Preferred Plus Service EPP900B2 One-year Epson Preferred Plus SpectroProofer EPPSPB1

*This product uses only genuine Epson-brand cartridges. Other brands of ink cartridges and ink supplies are not compatible and, even if described as compatible, may not function properly.

1 Ink lightfastness rating based on accelerated testing of prints on specialty media, displayed indoors, under glass. Actual print stability will vary according to media, printed image, display conditions, light intensity, humidity and atmospheric conditions. Epson does not guarantee longevity of prints. For maximum print life, display all prints under glass or lamination or properly store them. Visit www.wilhelm-research.com for the latest information. | 2 Print times are based upon print engine speeds only. Total throughput depends upon front-end driver/RIP, flie size, printing resolution, ink coverage, network speed, etc. Normal is for prints imaged using 1440 x 720 high-speed mode. | 3 Ink used in conversion varies considerably based on temperature and other factors. | 4 Carridge yields vary considerably based on images printed, print settings, paper type, frequency of use and temperature. For print quality, a variable amount of ink remains in the cartridge after the "replace cartridge" indicator comes on. The printer ships with full cartridges and part of the ink from the first cartridges is used for priming the printer. | 5 High-volume cutting of canvas and heavy media stocks may require frequent cutter replacement. | 6 Allowed by printer driver for Mac® and PC. Application, version of application and operating system version may limit maximum length. | 7 For the latest drivers, visit www.epson.com/support

Better Products for a Better Future

eco.epson.com





pson America, Inc. Epson Canada Limited

3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

EPSON, Epson ESC/P, PrecisionCore, SpectroProofer, SureColor and TFP are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and UltraChrome HDX are trademarks of Seiko Epson Corporation. BorderFree is a registered trademark and Epson Preferred is a service mark of Epson America, Inc. Apple, Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-50253 9/15